

## **SUPPLEMENT TO CERTIFICATE No. CF5228 SUPPLEMENT No. 523695**

This supplement is issued as an amendment to the Certificate of which it constitutes an integral part. It should be read in conjunction with the Certificate and any other supplements in force at the time.

### **Doorpac Ltd**

**2 Ranskill Court, Sheffield, S9 5FZ, United Kingdom**  
**Tel:0114 2561615**

#### **CERTIFIED PRODUCTS**

Doorpac Ltd – CF5228

#### **SCOPE OF SUPPLEMENT**

- To permit the use of single-action, single-leaves with doors 4 mm proud of the frame
- To permit the use of single-action, single-leaves, and pairs with doors 1 mm proud of the frame

#### **Single-Action, Single-Leaves with Doors 4 mm Proud of the Frame**

CF5228 single-action, single-leaf door assemblies, complete with the opening face of the leaf up to 4 mm proud of the opening face of the frame are permitted in accordance with the following door leaf, frame and intumescent specification requirements:

<b>Door leaf Requirements</b>	
Door Leaf:	CF5228 compliant door leaf construction
Configuration:	Single-action, single-leaves only (latched or unlatched)
Dimensions:	Maximum Leaf Height: 2196 mm (at 924 mm wide)
	Maximum Leaf Width: 997 mm (at 2040 mm high)
	Maximum Leaf Area: 2.03m <sup>2</sup>
Notes:	The door leaf shall include minimum 7 mm thick hardwood lippings to all four door leaf edges with a minimum density of 640kg/m <sup>3</sup> .



**CXY93870-1**

**Page 1 of 2**

## SUPPLEMENT TO CERTIFICATE No. CF5228 SUPPLEMENT No. 523695

This supplement is issued as an amendment to the Certificate of which it constitutes an integral part. It should be read in conjunction with the Certificate and any other supplements in force at the time.

### Frame Requirements:

Material:	MDF (minimum 760 kg/m <sup>3</sup> density) or Softwood / Hardwood (minimum 510 kg/m <sup>3</sup> density)	
Dimensions:	Lining:	Minimum 100 mm wide by 30 mm thick
	Stop:	Minimum 25 mm wide by 14 mm thick

### Intumescent Seal Requirements:

Supplier:	Pyroplex
Reference:	Rigid Box Intumescents (CF355)
Dimensions:	15 mm wide by 4 mm thick
Notes:	The frame jambs and head shall each include 1No. intumescent seal, as specified above, positioned 12 mm from the opening face of the frame.

All other scope relating to doorset design and configuration shall comply with CF5228 accordingly.

### Single-Action, Single-Leaves and Pairs with Doors 1 mm Proud of the Frame

CF5228 single-action, single-leaf and single-action, double-leaf assemblies may be installed with the opening face of the door leaves up to 1 mm proud of the opening face of the frame, subject to all other scope relating to doorset design and configuration being fully compliant with CF5228.

Issued for and on behalf of CERTIFIRE



P Duggan – Manager

Issued: 18<sup>th</sup> October 2024  
Valid to: 17<sup>th</sup> October 2029



CXY93870-1

Page 2 of 2