



---

**SUPPLEMENT TO CERTIFICATE No.  
CAF 5228  
SUPPLEMENT No. 534889**

---

This supplement is issued as an amendment to the Certificate of which it constitutes an integral part. It should be read in conjunction with the Certificate and any other supplements in force at the time.

**Doorpac Ltd**  
**2 Ranskill Court, Sheffield, South Yorkshire, S9 5FZ**  
**Tel: 0114 256 1615**

**CERTIFIED PRODUCTS**

Doorpac Limited – CF5228

**SCOPE OF SUPPLEMENT – POCKLINGTON COURT – LONDON**

To permit the use of tubular latches, in conjunction with a maximum 20 mm diameter spindle recess in accordance with the following specification:

- CF5228 door assemblies only
- Tubular latches will fully comply with the requirements of CF5228
- Maximum 20 mm diameter spindle hole recess.
- Consort CH499 satin stainless steel lever handles with steel bolt through, back to back fixings
- 2 mm thick graphite intumescent sheet material to the circumference of the spindle recess (both faces of the door leaf).
- 1 mm thick graphite intumescent sheet material to fully wrap the tubular latch case.

**All other scope relating to doorset design and configuration should comply with CF5228 accordingly.**

Issued for and on behalf of CERTIFIRE

P Duggan – Manager

Issued: 11<sup>th</sup> September 2023  
Valid to: 10<sup>th</sup> September 2028

