



Size Given Is The **Machined** Aperture Size In The Door

For FD30 & FD60 Doors The Machined Aperture Is Fitted A Hardwood Security Bead With A 6mm Integral Liner. The Finished Aperture Is Therefore Reduced By 12mm In Width & Height

For FD30 Doors The Visible Glass Area Is Reduced By A Further 30mm In Width & Height Due To The Bead Thickness

For FD60 Doors The Visible Glass Area Is Reduced By A Further 50mm In Width & Height Due To The Bead Thickness

| Fire Rating | Glass | Glazing System |
|-------------|----------------|----------------|
| FD30 | Pyrobelite 9EG | DP15959 |
| FD60 | Pyrobel 16EG | DP15983 |

| | Width | Height |
|-------------------|-------|--------|
| Machined Aperture | 162 | 1492 |
| Lined Aperture | 150 | 1480 |
| Glass | 145 | 1473 |

Do Not Scale.

If In Doubt Ask!

Description: Doorpac Standard Aperture - PAS24 (DDA Compliant) - 150 x 1480mm - 150mm Top & Side Margins - FD30 & FD60 Machining

| | | | | |
|-------------------------|--------------------|-----------|----------------------------|---------------------------------------------------------------------------------------------------|
| Drawn By: P. Brash | Approved: Approved | Revision: | Date: 27/01/2026 | Drawing No: DP21402 |
| Size: 1981/ 2040mm Door | Tolerance: ± 0.5mm | | Fire Rating: FD30S & FD60S | |
| Job No: | © Doorpac Ltd | | Rev01 | doorpac creating the perfect opening Unit 6, Ranskill Court, Sheffield, S9 5FZ |