



Quality Standard Of Glazed Aperture To Work Instruction - WI_21

Only Employees With A Signed Training Record For This Glazing System To Use This Glazing System

Approved Glass

Glass Type	Glass Certificate	Material Specification For Glass	Beading Drawing	Material Specification For Beading	Maximum Width (mm)	Maximum Height (mm)	Maximum Area (m ²)	Machined Aperture Width 10mm Larger & Height 12mm Larger Than Glass	Lined Aperture Width 5mm Larger & Height 7mm Larger Than Glass
6mm Pyrostem (Wired)	CF5954	MS_006	DP16447	MS_007	517(W) @1500(H)	1773(H) @250 (W)	0.78@517(W) 0.43@1773 (H)		

Do Not Scale.

If In Doubt Ask!

Description: Glazing System - FD60 - 6mm Pyrostem Glass (Wired) - 54mm Door - Bolection Bead

© Doorpac Ltd

Drawn By: O BOOY	Approved: Approved	Date: 13/01/2026	Cert / FoA Ref: CF5954	Drawing No: DP16446	doorpac
Size: As Above	Rev:	Fire Rating: FD60S			Unit 6, Ranskill Court, Sheffield, S9 5FZ
Job No:	Tolerance: ±0.25mm				