

General Measurements From The Bottom Of The Door For
Standard 2040mm Doors:

Eye Viewer Height - 1450mm (Max For Fire Certification)
Roller Night Latch Height - 1100mm
Lever Height - 1020mm
Cylinder Height For Dead Locks - 1020mm
Disabled WC Lever Height - 920mm
Disabled Additional Eye Viewer - 1050mm

Non Standard Height Doors - Positions As Above Or Mid
Height As Appropriate. Other Ironmongery As Appropriate
Unless Specified In Advance By The Customer

Height To Bottom Of Pull Handles:

300mm Handle - 1000mm
425mm Handle - 938mm
600mm Handle - 850mm

Height to Lock On Door Fitted With A Pull Handle:
72mm Below Bottom Of Handle

Kick Plate Sizes:


926mm Doors = 886 x 150mm
826mm Doors = 786 x 150mm

Gives Approximately 10mm Margin Between The Door
Stops And The Edge Of The Kick Plate And 5mm Margin
Between The Kick Plate And The Bottom Of The Door

Do Not Scale.

If In Doubt Ask!

Description: **Standard Metric Ironmongery Positions**

Drawn By: O BOOY	Approved: Approved	Revision:	Cert / FoA Ref:	Date: 23/05/2025	Drawing No:	 <p>Unit 6, Ranskill Court, Sheffield, S9 5FZ</p>
Size: 2040mm Door	Tolerance: +/- 0.25mm			Fire Rating:	DP16658	
Job No:	© Doorpac Ltd				Rev04	